



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D350-636-011
Job Sheet 176610



Part No: D350-636-011

Job Qty: 1 ea

Part Name: Skidtube LH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 4/26/18

Job Tracking No:

Due Date: 5/21/18

Created By: Marie Lajeunesse

Type: SOLD

Description:

Note: D2750-041 REV G SHEETS 1,2,4,8 IPP Rev:I 02.09.25 IPP Rev:J 06-03-23 As per Rev D IPP Rev:K 06-07.13
As per dsi9343 IPP Rev:L 07-07-28 Added SS Wearplates(Rev E) JLM Ver:EC IPP Rev:M 08-04-22 DD
verified:EC IPP Rev:N 08-09-23 revF DD verified:ec IPP Rev:O 09-02-06 per PAR09-010 DD ver:EC IPP
Rev:P 10.06.22 revise seq110 DD ver:EC IPP Rev:Q 10.10.01 as per IIN revH DDver:EC IPP REV:R
13.08.27 PER ECN13-594 DD VERF:JLM

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea		5/21/18	0.00	0.00	Start Up Skidtubes-1		m64
110	Skidtubes	1 pcs		5/21/18	0.00	4.55	Skidtubes-4		m64
120	QC	1 pcs		5/21/18	0.00	0.00	QC10		
130	QC	1 pcs		5/21/18	0.00	0.00	QC5		
140	HandFinish	1 pcs		5/21/18	0.00	0.93	HandFinish1		SA 18-06-07
150	QC	1 pcs		5/21/18	0.00	0.00	QC7-2		
160	Skidtubes	1 pcs		5/21/18	0.00	4.55	Skidtubes-4		
170	QC	1 pcs		5/21/18	0.00	0.00	QC10		
180	QC	1 pcs		5/21/18	0.00	0.00	QC5		
190	HandFinish	1 pcs		5/21/18	0.00	0.93	HandFinish2		BEB 18-06-28
200	SprayPaint	1 pcs		5/21/18	0.00	0.91	Spray Paint		AS JUL 15 2018
205	Outsource	1 pcs		5/21/18			ATE003-VC		
210	QC	1 pcs		5/21/18	0.00	0.00	QC14		
230	HandFinish	1 pcs		5/21/18	0.00	0.93	HandFinish4		BEB 18-07-18
240	QC	1 pcs		5/21/18	0.00	0.00	QC5		
250	Packaging	1 pcs		5/21/18	0.00	0.00	Packaging1-3		JUL 26 2018
260	QC	1 pcs		5/21/18	0.00	0.00	QC4		JUL 26 2018
265	DC	1 pcs		5/21/18	0.00	0.00	DC		
270	Packaging	1 pcs		5/21/18	0.00	0.00	Packaging3-1		JUL 26 2018
280	QC21-FG	1 Ea		5/21/18	0.00	0.00	QC21		JUL 26 2018

Part Op 110 - 1- Pick D2600-3 Bent 2- Deburr FWD and AFT ends, remove bending marks. Scribe batch# inside AFT end per dwg
Descriptions: D2750-1 3- Drill pilot holes for blade fitting bolt holes using DT8983. Start with 3/16", then open to 0.500" using center drill
then ream holes using 0.500" reamer. PIN first side. Repeat process on second side. ***ENSURE PROPER
POSITIONING FWD BEND MUST BE FACING UP WHEN DRILLING FIRST SIDE*** Drill pilot holes as per Dwg D2750
sheet 4 (D2750-1 details). Drill using drill Jig DT8150 & DT8863A for 2nd side only DT8863B for first side (detail B) 4-
Locate DT8330 off of blade fitting bolt holes and drill pilot holes for blade fitting. Open to 0.500" using hole saw. VERIFY
AND RECORD FWD BEND ANGLE. 5-Drill pilot holes for wearplates as per Dwg D2750 using DT8108 open to 0.297".
6-Open up holes of Detail A to 0.297" (total of 2 holes per side) 7-Weld D2744 Cap as per Dwg D2750 and QSI 004.Fill
grooves in bend left from bending as per QSI 004 A/R Aluminum Rod batch: 138834 8-Grind welds flush as per Dwg
D2750
160 - 1-Open up holes using hole saw of Detail C and ground handling to 0.625" (total of 8 holes per side) as per dwg
D2750. 2-Open up holes using hole saw of Detail B to 0.750" (total of 4 holes per side) as per dwg D2750. 3- Open float

[illegible]

hole using un-bit to 0.500" (4 per side) 4-Chamfer holes of Detail B, C, ground handling and float holes per dwg D2750 (welding instructions on sheet 8) 5-Debur and blow out all chips from inside of tube 6- Prepare tube for welding, remove alodine as required. 7-Bond web D2739 in place as per QSI 015, let cure for 12hrs. A/R Sikaflex-291 batch: 432013 exp. date: 190306 ***ATTN: USE I-BEAM LOCATION AID (BLADE FITTING)*** 8- Weld spacers D3490-1, D3490-3 and D2743 as per dwg D2750 & QSI004 (welding instructions on sheet 8) A/R Aluminum Rod batch: 138834 9- At section AJ-AJ drill out x-bolt spacer to 0.404" 10-Grind welds flush as per Dwg D2750 11-Spot face ground handling holes section (total of 4 places per side) as per dwg D2750 12-Debur holes, ensure tube is free of all scratches before sending to paint.

180 - ***VERIFY C'BOARD IS GOOD***

190 - Re-alodine tube as per QSI 005 section 4.1.2.1 do not acid etch.

200 - 1- PRIME AS PER DWG AND QSI 005 4.2 PRIMER PRC DESOTO 515X349 BATCH: 138862 2-

PAINT WHITE AS PER DWG AND QSI 005 4.2 PAINT BATCH: 138886

210 - Inspect for foreign object per QSI 024

230 - 1- Install inserts as per Dwg D2750 2- Inspect for Foreign Objects 3- Install blade fitting D3488-041, wearshoes and ground handling hardware as per dwg D2750 SIKAFLEX 241 BATCH: 4138787 EXP DATE: 18/12 4-

Assemble o'ring to plug as per dwg D3492 and apply o'ring lube A/R 55-o'ring lube batch: 4138843 5- Coat all exposed fasteners with "LPS Procyon" batch: 4133680

260 - *****ensure antiseize is on AN8C21A bolts*****

265 - record fwd angle: 89.9 Photocopy blue file and type labels per PPP D350-636-011 CHG 007

270 - Package as per PPP D350-636-011 Location : FG072

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
D2600-3-BENT-LH	Extrusion Bent LH	1 Ea (1 ea)	90-Start up Operation	<u>5073819</u>
D2744	Cap	1 Ea (1 ea)	90-Start up Operation	<u>5063542</u>
D2739	350 I-Beam	1 Ea (1 ea)	160-Skidtubes	<u>5081150</u>
D2743	Crossbolt Spacer	8 Ea (8 ea)	160-Skidtubes	<u>5082661</u>
D3490-1	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	<u>5065863</u>
D3490-3	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	<u>5066264</u>
AN3C5A	Bolt	34 Ea (34 ea)	230-HandFinish	<u>5057153</u>
AN3C6A	Bolt	4 Ea (4 ea)	230-HandFinish	<u>5076000</u>
AN6C44A	Bolt	4 Ea (4 ea)	230-HandFinish	<u>5006333-1</u>
AN8C35A	Bolt	1 Ea (1 ea)	230-HandFinish	<u>FM137203</u>
D2745	Bushing	8 Ea (8 ea)	230-HandFinish	<u>5082489</u>
D3488-041	Blade Fitting LH	1 Ea (1 ea)	230-HandFinish	<u>5070841</u>
D3492-1	Plug	8 Ea (8 ea)	230-HandFinish	<u>5077552</u>
D3492-3	Plug	8 Ea (8 ea)	230-HandFinish	<u>5072782</u>
D3535-25	Wearplate Center	1 Ea (1 ea)	230-HandFinish	<u>5080560</u>
D3536-25	Gasket Center	1 Ea (1 ea)	230-HandFinish	<u>5081731</u>
D3537-1	Wearpad	3 Ea (3 ea)	230-HandFinish	<u>5053117</u>
D3631-1	Washer	8 Ea (8 ea)	230-HandFinish	<u>5058407</u>
D3791-1	Wearpad	1 Ea (1 ea)	230-HandFinish	<u>5071379</u>
D3793-1	Wearplate Fwd	1 Ea (1 ea)	230-HandFinish	<u>5070839</u>
D3793-3	Wearplate Aft	1 Ea (1 ea)	230-HandFinish	<u>5072081</u>
D3794-1	Gasket Fwd	1 Ea (1 ea)	230-HandFinish	<u>5071975</u>
D3794-3	Gasket Aft	1 Ea (1 ea)	230-HandFinish	<u>5046513</u>
MS21043-6	Nut	4 Ea (4 ea)	230-HandFinish	<u>5083545</u>
MS21083C8	Nut	1 Ea (1 ea)	230-HandFinish	<u>5050046-1</u>
NAS1149C0332R	Washer	38 Ea (38 ea)	230-HandFinish	<u>5056493</u>
NAS1149C0832R	Washer	1 Ea (1 ea)	230-HandFinish	<u>4138409-121</u>
NAS1515H3L	Washer	4 Ea (4 ea)	230-HandFinish	<u>5036714</u>
NAS1611-010	O-Ring	8 Ea (8 ea)	230-HandFinish	<u>5049970</u>
NAS1611-013	O-Ring	8 Ea (8 ea)	230-HandFinish	<u>5077839</u>
ALS4-1032-225	Rivnut	38 Ea (38 ea)	230-HandFinish	<u>5058138</u>
AN8C21A	Bolt	2 Ea (2 ea)	250-Packaging	<u>FM137162</u>
D2741	Replacement Blade	1 Ea (1 ea)	250-Packaging	<u>5068565</u>
D3493-1	Washer	2 Ea (2 ea)	250-Packaging	<u>5067105</u>
D3532-1	Spacer	2 Ea (2 ea)	250-Packaging	<u>5020421</u>
MS21083C8	Nut	2 Ea (2 ea)	250-Packaging	<u>5050046</u>
NAS1149D0863J	Washer	2 Ea (2 ea)	250-Packaging	<u>4125635</u>

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	D2600-3-BENT-LH	1	3	0

160-Skidtubes	D2744	1	87	0
	D2739	1	16	0
	D2743	8	134	0
	D3490-1	4	28	0
230-HandFinish	D3490-3	4	11	0
	ALS4-1032-225	38	5,580	0
	AN3C5A	34	1,993	0
	AN3C6A	4	286	0
	AN6C44A	4	363	0
	AN8C35A	1	52	0
	D2745	8	137	0
	D3488-041	1	5	0
	D3492-1	8	120	0
	D3492-3	8	45	0
	D3535-25	1	27	0
	D3536-25	1	35	0
	D3537-1	3	126	0
	D3631-1	8	955	0
	D3791-1	1	23	0
	D3793-1	1	11	0
	D3793-3	1	19	0
	D3794-1	1	24	0
	D3794-3	1	32	0
	MS21043-6	4	212	0
	MS21083C8	1	137	0
	NAS1149C0332R	38	6,209	0
	NAS1149C0832R	1	73	0
	NAS1515H3L	4	211	0
	NAS1611-010	8	601	0
	NAS1611-013	8	397	0
250-Packaging	AN8C21A	2	107	0
	D2741	1	54	0
	D3493-1	2	34	0
	D3532-1	2	46	0
	MS21083C8	2	137	0
	NAS1149D0863J	2	125	0

Part Specifications

Specifications could not be found.

Kim Johnston

From: Sonia Quirion
Sent: Thursday, July 19, 2018 11:16 AM
To: Kim Johnston
Subject: L/B

s076433
176610 - D350-636-011
X1

Part Number: D350-636-011/-011GB/-012/-012GB

Description: SKIDTUBE STD LH/RH, FLOAT COMPATIBLE

[illegible]